## SUPREME SINGLE HUNG WINDOW



#### Features & Benefits

- Energlas® Plus (triple glaze) glass available with grills and SDL (Simulated Divided Lite)
- Overall glass thickness increased to 1" for triple glazed units, to allow for improved energy efficiency and grill options (3/4" still the default for double glazed)
- Triple seal weather-stripping for increased weather performance
- Available with Integral 1½" brickmould
- Available with add-on brickmoulds
- New Integral <sup>3</sup>/<sub>4</sub>" return with optional <sup>1</sup>/<sub>2</sub>" return available
- Auto and manual night lock options available
- · Available in white and tan uPVC
- All standard colors or custom colors available
- Sloped screen support to improve water performance/drainage
- Installation prep-holes have been relocated to balance chamber to allow for easier installation and a cleaner look
- Improved thermal performance (ER & U values), see chart to right
- Improved structural performance LC-PG65-H (size tested 44x78)
- · Heavy duty t-mullion



## THE RIGHT CHOICE FOR PERFORMANCE & QUALITY

We've upgraded our 2016 Supreme Single Hung window to offer optimum performance. Our new design offers improved thermal performance (ER & U values) and improved structural performance.

Glass Options	Energy Rating	U-value (metric)	U-value (imperial)	Solar Heat Gain Coefficient	Visible Transmittance	Condensation Resistance	Canadian Energy Star Zones
Energlas Plus Krypton LSG	32	0.97	0.17	0.25	0.44	71	1,2,3
Energlas Plus Krypton	43	1.08	0.19	0.48	0.57	70	1,2,3
Energlas Plus Argon LSG	27	1.19	0.21	0.25	0.44	69	1,2,3
Energlas Plus Argon	39	1.25	0.22	0.48	0.57	67	1,2,3
Energlas-LSG	23	1.53	0.27	0.31	0.55	57	1
LoE/Argon-LSG	21	1.65	0.29	0.31	0.56	56	NO
Energlas	35	1.65	0.29	0.55	0.64	50	1,2,3
LoE/Argon	32	1.76	0.31	0.55	0.64	47	1,2

# SUPREME SINGLE HUNG WINDOW



### SUPREME SINGLE HUNG WINDOW

- 1 34" or 1" overall glazing
- 2 1½" Brickmould/J-trim Integral
- 3 Glazing upstand (to allow SDL)
- 4 Slopped seam support for better drainage
- 5 Triple weather seal
- 6 Frame indent for installation screws
- 7 Integral ¾" drywall return

#### SUPREME'S KEY FEATURES

- Heavier glazing stop than Select Series
- Chambered glazing upstand on frame and sash (SDL friendly)
- Heavier sash lock system
- Self locking available

- Coil balance
  - Concealed tilt latch
  - Head close out
  - Lifetime warranty

